



Coax Bias Tee						
Frequency Range (GHz)	Insertion Loss (DB) Max.	Voltage (Volts) Max.	VSWR Max.	Outline Number	Connectors	Model Number
0.0001 - 4	0.5	50	1.20:1	DCB1		
0.0001 - 4	0.6	100	1.25:1	DCB2		
0.001 - 6	0.7	100	1.30:1	DCB3		
6 - 12.4	0.5	100	1.35:1	DCB4		
6 - 12.4	0.7	500	1.50:1	DCB5		
0.3 - 18	0.5	50	1.30:1	DCB6		
0.01 to 6	0.5	50	1.35		N	WA6046/6
0.01 to 6	0.5	50	1.35		SMA	WA6055H/6
0.01 to 18	0.8	50	1.5		N	WA6046
0.01 to 18	0.8	50	1.5		SMA	WA6055H
0.01 to 6	0.5	100	1.35		N	WA7046/6
0.01 to 6	0.5	100	1.35		SMA	WA7055H/6
0.01 to 18	0.8	100	1.5		N	WA7046
0.01 to 18	0.8	100	1.5		SMA	WA7055H
0.01 to 6	0.5	200	1.35		N	WA8046/6
0.01 to 6	0.5	200	1.35		SMA	WA8055H/6
0.01 to 18	0.8	200	1.5		N	WA8046
0.01 to 18	0.8	200	1.5		SMA	WA8055H